

## JTHW-A 型手摇绞车

### JTHW-A WINCH SPECIFICATIONS

规格 Model	额定载荷 Rated capacity (lb)	试验载荷 Test load (KN)	单速/双速 Single speed/ Double speed	速比 Transmission ratio	最大手摇力 (N) Hand operated strength	净重 (KG) Net weight
600lb	600	4.1	单速 Single	2.9:1	70	2.4
800lb	800	5.4	单速 Single	3.7:1	75	2.5
1000lb	1000	6.8	单速 Single	4.2:1	85	2.8
1200lb	1200	8.2	单速 Single	4.2:1	100	2.8
1400lb	1400	9.5	单速 Single	4.2:1	120	2.8
2000lb	2000	13.6	双速 Double	10.35:1 4.5:1	150	5.9
2500lb	2500	17	双速 Double	11.5:1 5:01	160	6.4



## JTHW-C 型手摇绞车

### JTHW-C WINCH SPECIFICATIONS

规格 Model	额定载荷 Rated capacity (lb)	试验载荷 Test load (KN)	速比 Transmission ratio	手摇力(N) Hand operated strength	净重 (KG) Net weight
1200lb	1200	8	4.2:1	180	3.7
1800lb	1800	12	5:01	190	8.1
2600lb	2600	17.5	10:01	190	10.3



## JTHW-B 型手扳式绞车

### JTHW-B LEVER WINCH SPECIFICATIONS

规格 Model	额定载荷 Sate Working Load (T)	试验载荷 Teat load (KN)	适用钢丝绳 直径(MM)* 长度(M) Adopted Wire rope Dia*Length	速比 Speed ratio	连杆作用 最大长度 (MM) THE Max. length of link-pole action	最小手扳力 (N) Min force of hand turn	净重 (KG) Net weight
0.5T	0.5	6.125	6.3*40	4.33:1	350	120	14.4
1T	1	12.25	8*40	12.19:1	350	120	19.7
2T	2	24.5	9*40	22.68:1	350	130	25.1
3T	3	36.75	12.5*40	29.16:1	350	180	44.3

